

NR2

BERTJAN POT



NR2 by Bertjan Pot is an elegant and bright bubble of white or black thread. The lattice pattern creates a fine web that shines and glimmers in the light. The fine web is oval-shaped and bears the signature style of Bertjan Pot; designs created from an experiment with different materials. The integrated LED lamp in NR2 subtly diffuses a soft and magical glow around the room. NR2 is available in two different colours and sizes.

Detailing




NR2's lattice patterned web of clean lines falls into place in any modern interior and brings an element of calmness in a maximalist's home.

Colours



Just Black





White

NR2 / Large

Dimensions

Ø75cm | 29.5"



Product

WIDTH 75cm | 29.5"

HEIGHT 53cm | 20.9"

DEPTH 75cm | 29.5"

DIAMETER 75cm | 29.5"

WEIGHT NETTO 1.2kg | 2.65lbs

Packaging

WIDTH 78cm | 30.7"

HEIGHT 69cm | 27.2"

CUBAGE 0.42m³ | 14.82ft³

LENGTH 78cm | 30.7"

WEIGHT 8kg | 17.64lbs

Technical CE

MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

ENERGY LABEL

B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

SHAPE

Oval

INPUT VOLTAGE

120-277V

FREQUENCY

50/60

MAX POWER CONSUMPTION

26W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black, White

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CHROM X

0.48

CHROM Y

0.41

COLOUR TEMPERATURE

2468 K

CRI

81

LIGHT DIRECTION

All directions

LIGHT OUTPUT

1047 lm

DIMMING & LIGHTING CONTROL

Mains and/or 1-10V dimmable (trailing edge / reverse phase)

See last page for more information about the dimming possibilities.



*Technical UL***MATERIAL**

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

ENERGY LABEL

B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

SHAPE

Oval

INPUT VOLTAGE

120-277V

FREQUENCY

50-60

MAX POWER CONSUMPTION

26W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black, White

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CHROM X

0.48

CHROM Y

0.41

COLOUR TEMPERATURE

2468 K

CRI

81

LIGHT DIRECTION

All directions

LIGHT OUTPUT

1047 lm

DIMMING & LIGHTING CONTROL

Mains and/or 1-10V dimmable (trailing edge / reverse phase)


See last page for more information about the dimming possibilities.



NR2 / Medium

Dimensions

55cm | 21.7"



Product

WIDTH 55cm | 21.7"
HEIGHT 40cm | 15.7"
DEPTH 55cm | 21.7"
DIAMETER 55cm | 21.7"
WEIGHT NETTO 0.9kg | 1.98lbs

Packaging

WIDTH 57cm | 22.4"
HEIGHT 52cm | 20.5"
CUBAGE 0.17m³ | 5.97ft³
LENGTH 57cm | 22.4"
WEIGHT 3.7kg | 8.16lbs

Technical CE

MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

ENERGY LABEL

B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

SHAPE

Oval

INPUT VOLTAGE

208-277V

FREQUENCY

50/60

MAX POWER CONSUMPTION

12W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black, White

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

COLOUR TEMPERATURE

2700 K

CRI

82

LIGHT DIRECTION

All directions

LIGHT OUTPUT

450 lm

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



Technical UL

MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

ENERGY LABEL

B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

SHAPE

Oval

INPUT VOLTAGE

120V

FREQUENCY

50/60

MAX POWER CONSUMPTION

12W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black, White

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

COLOUR TEMPERATURE

2700 K

CRI

82

LIGHT DIRECTION

All directions

LIGHT OUTPUT

450 lm

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



Dimming & Lighting Control

Mains and/or 1-10V dimmable (trailing edge / reverse phase)

Compatible models: Large CE, Large UL

Mains, Trailing edge, Reverse phase

The luminaire is dimmable by using an external Electronic Low Voltage dimmer. The dimmer is usually mounted on an existing wall socket and there is no need to change your home's wiring. On the dimmer it should show that it is a LED dimmer, suitable for 5 Watts or lower and C-type capable. Dimming is less fluent and can come with some flicker, a beep or a buzz.

Compatible models: Medium CE, Medium UL
