

NR2

BERTJAN POT



NR2 by Bertjan Pot is an elegant and bright bubble of white or black thread. The lattice pattern creates a fine web that shines and glimmers in the light. The fine web is oval-shaped and bears the signature style of Bertjan Pot; designs created from an experiment with different materials. The integrated LED lamp in NR2 subtly diffuses a soft and magical glow around the room. NR2 is available in two different colours and sizes.

Detailing




NR2's lattice patterned web of clean lines falls into place in any modern interior and brings an element of calmness in a maximalist's home.

Colours



Just Black




White

NR2 / Large

Dimensions

Ø75cm | 29.5"



Product

WIDTH 75cm | 29.5"

HEIGHT 53cm | 20.9"

DEPTH 75cm | 29.5"

DIAMETER 75cm | 29.5"

WEIGHT NETTO 1.2kg | 2.65lbs

Packaging

WIDTH 78cm | 30.7"

HEIGHT 69cm | 27.2"

CUBAGE 0.42m³ | 14.82ft³

LENGTH 78cm | 30.7"

WEIGHT 8kg | 17.64lbs

Technical CE

MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

120-277

MAX POWER CONSUMPTION

26W

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

CANOPY

Pebble II Black, ABS

CHROM Y

0.41

CRI

81

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Oval

FREQUENCY

50/60

DIMMABLE

Yes

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CHROM X

0.48

COLOUR TEMPERATURE

2468 K

LIGHT DIRECTION

All directions

LIGHT OUTPUT

1047 lm



*Technical cULus***MATERIAL**

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

ENERGY LABEL

Energy Label B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

SHAPE

Oval

INPUT VOLTAGE

120-277

FREQUENCY

50-60

MAX POWER CONSUMPTION

26W

DIMMABLE

Yes

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CANOPY

Pebble II Black, ABS

CHROM X

0.48

CHROM Y

0.41

COLOUR TEMPERATURE

2468 K

CRI

81

LIGHT DIRECTION

All directions

LIGHT OUTPUT

1047 lm



NR2 / Medium

Dimensions

55cm | 21.7"



40cm | 15.7"

Product

WIDTH 55cm | 21.7"

HEIGHT 40cm | 15.7"

DEPTH 55cm | 21.7"

DIAMETER 55cm | 21.7"

WEIGHT NETTO 0.9kg | 1.98lbs

Packaging

WIDTH 57cm | 22.4"

HEIGHT 52cm | 20.5"

CUBAGE 0.17m³ | 5.97ft³

LENGTH 57cm | 22.4"

WEIGHT 3.7kg | 8.16lbs

Technical CE

MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

208-277

MAX POWER CONSUMPTION

12W

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

CANOPY

Pebble II Black, ABS

CRI

82

LIGHT OUTPUT

450 lm

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Oval

FREQUENCY

50/60

DIMMABLE

Yes

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

All directions



Technical cULus

MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

ENERGY LABEL

Energy Label B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

SHAPE

Oval

INPUT VOLTAGE

120

FREQUENCY

50/60

MAX POWER CONSUMPTION

12W

DIMMABLE

Yes

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CANOPY

Pebble II Black, ABS

COLOUR TEMPERATURE

2700 K

CRI

82

LIGHT DIRECTION

All directions

LIGHT OUTPUT

450 lm



Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

DIMMER TYPE

Mains dimmable (trailing edge / reverse phase)

LOAD TYPE

Capacitive load (C-Type)
