moooi

Raimond II Tensegrity

The Raimond Tensegrity is a floor lamp made from elegant metal, complemented with the sturdy earthiness of wood. Tensegrity is a term that was first described by Buckminster Fuller as an architectural term. It refers to the interconnected wooden structure that uses tension and pressure to keep its shape. The beauty of the Raimond Tensegrity lies not only in its contrasting materials, but also in the trigonometric harmony of both structures. Mathematical perfection times two.

Detailing



Raimond Puts never saw his final design. But, together with Raimond's wife, artist & designer Tis Ernst, Moooi completed the Raimond Tensegrity.

Colours



Stainless steel

Raimond II Tensegrity / Raimond II Tensegrity, R61

Dimensions







Product

width 61cm | 24" неight 80cm | 31.5" depth 61cm | 24" diameter 61cm | 24" weight netto 10kg | 22.05lbs

Packaging

width 75cm | 29.5" неіднт 75cm | 29.5" сиваде 0.42m³ | 14.9ft³ length 75cm | 29.5" weight 10kg | 22.05lbs

Technical CE / CU

MATERIAL

Stainless Steel Sphere (indoor use, not resistant to marine environemts) with PMMA lenses, wooden legs and leather straps

ENERGY LABEL	LIGHTSOURCE TYPE
В	LED
LIGHTSOURCE INCLUDED	NUMBER OF LIGHTSOURCES
Yes	162
INPUT VOLTAGE	FREQUENCY
120-250V	50/60
MAX POWER CONSUMPTION	LAMPHOLDER
17W	LED (Solid state)
LIFETIME	CABLE COLOUR
50000 hours	Transparent with tinned cores
CABLE LENGTH	SWITCH
500cm 196.9"	In line dimmer switch integrated in power supply
	housing
COLOUR TEMPERATURE	CRI
2523 K	92
LIGHT DIRECTION	LIGHT OUTPUT
All directions	1134 lm
DIMMING & LIGHTING CONTROL	
Dimmer on power cord	

See last page for more information about the dimming possibilities.

Raimond II Tensegrity / Raimond II Tensegrity, R89

Dimensions

89cm | 35"





Technical CE / CU

MATERIAL

Stainless Steel Sphere (indoor use, not resistant to marine environemts) with PMMA lenses, wooden legs and leather straps

ENERGY LABEL

В

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE 120-250V

MAX POWER CONSUMPTION 26W

LIFETIME 50000 hours

CABLE LENGTH 500cm | 196.9"

COLOUR TEMPERATURE 2523 K

LIGHT DIRECTION All directions

LIGHTSOURCE TYPE I FD

Product

width 89cm | 35"

DEPTH 89cm | 35" DIAMETER 89cm | 35"

ныднт 113ст | 44.5"

NUMBER OF LIGHTSOURCES 252

FREQUENCY 50/60

LAMPHOLDER LED (Solid state)

CABLE COLOUR Transparent with tinned cores

SWITCH In line dimmer switch integrated in power supply housing

CRI 92

LIGHT OUTPUT 1744 lm

Packaging

width 104cm | 40.9" **ныднт** 104cm | 40.9" **CUBAGE** 1.12m³ | 39.72ft³ **LENGTH** 104cm | 40.9" **WEIGHT NETTO** 16kg | 35.27lbs **WEIGHT** 16kg | 35.27lbs

DIMMING & LIGHTING CONTROL

Dimmer on power cord

See last page for more information about the dimming possibilities.

Dimming & Lighting Control

Dimmer on power cord

Compatible models: Raimond II Tensegrity, R61 CE, Raimond II Tensegrity, R61 CU, Raimond II Tensegrity, R89 CE, Raimond II Tensegrity, R89 CU