

m o o o i

## Random Light II

BERTJAN POT



Random Light II transmits a feeling of simplicity, lightness and a touch of magic in a contemporary style. Due to how they're made, each Random Light is unique. They're never completely round, yet always beautifully transparent and delicate.

---


### *Detailing*



The open and random texture of the Random Light plays with shadow while it emits a soft glow.

---

### *Colours*





Black

White

# Random Light II / large

## Dimensions

Ø105cm | 41.3"



## Product

**WIDTH** 105cm | 41.3"  
**HEIGHT** 105cm | 41.3"  
**DEPTH** 105cm | 41.3"  
**DIAMETER** 105cm | 41.3"  
**WEIGHT NETTO** 2.5kg | 5.51lbs

## Packaging

**WIDTH** 110cm | 43.3"  
**HEIGHT** 110cm | 43.3"  
**CUBAGE** 1.33m<sup>3</sup> | 47ft<sup>3</sup>  
**LENGTH** 110cm | 43.3"  
**WEIGHT** 13.5kg | 29.76lbs

## Technical CCC

### MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

### ENERGY LABEL

A++ to E

### LIGHTSOURCE TYPE

Incandescent

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

1

### DIAMETER SHADE

105cm | 41.3"

### INPUT VOLTAGE

220-240V

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

60W

### LAMPHOLDER

E27

### RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

### LIFETIME

50000 hours

### CABLE COLOUR

Black

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### CANOPY

Pebble II Black, ABS, Pebble II White, ABS

### CRI

90

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

800 lm

### DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.*



## Technical CE

### MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

### ENERGY LABEL

A++ to E

### LIGHTSOURCE TYPE

Incandescent

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

1

### DIAMETER SHADE

105cm | 41.3"

### INPUT VOLTAGE

220-240V

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

60W

### LAMPHOLDER

E27

### RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

### LIFETIME

50000 hours

### CABLE COLOUR

Black

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### CANOPY

Pebble II Black, ABS, Pebble II White, ABS

### CRI

90

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

800 lm

### DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.*



---

## Technical UL

### MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

### ENERGY LABEL

A++ to E

### LIGHTSOURCE TYPE

Incandescent

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

1

### DIAMETER SHADE

105cm | 41.3"

### INPUT VOLTAGE

110-130V

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

60W

### LAMPHOLDER

E26

### RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

**LIFETIME**

50000 hours

**CABLE LENGTH**

400cm | 157.5"; 1000cm | 393.7"

**CRI**

90

**LIGHT OUTPUT**

800 lm

**CABLE COLOUR**

Black

**CANOPY**

Pebble II Black, ABS, Pebble II White, ABS

**LIGHT DIRECTION**

All directions

**DIMMING & LIGHTING CONTROL**

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.*

## Random Light II / medium

### Dimensions

Ø80cm | 31.5"



### Product

**WIDTH** 80cm | 31.5"**HEIGHT** 80cm | 31.5"**DEPTH** 80cm | 31.5"**DIAMETER** 80cm | 31.5"**WEIGHT NETTO** 1.8kg | 3.97lbs

### Packaging

**WIDTH** 87cm | 34.3"**HEIGHT** 87cm | 34.3"**CUBAGE** 0.66m<sup>3</sup> | 23.25ft<sup>3</sup>**LENGTH** 87cm | 34.3"**WEIGHT** 5.5kg | 12.13lbs

### Technical CCC

**MATERIAL**

Sphere from fiberglass with epoxy resin, chromed steel pendant

**ENERGY LABEL**

A++ to E

**LIGHTSOURCE INCLUDED**

Yes

**DIAMETER SHADE**

80cm | 31.5"

**FREQUENCY**

50/60

**LAMPHOLDER**

E27

**LIGHTSOURCE TYPE**

Incandescent

**NUMBER OF LIGHTSOURCES**

1

**INPUT VOLTAGE**

220-240V

**MAX POWER CONSUMPTION**

60W

**RECOMMENDED LIGHTSOURCE**

60W MAX type G, 10W LED light included

**LIFETIME**

50000 hours

**CABLE LENGTH**

400cm | 157.5"; 1000cm | 393.7"

**CRI**

90

**LIGHT OUTPUT**

800 lm

**CABLE COLOUR**

Black

**CANOPY**

Pebble II Black, ABS, Pebble II White, ABS

**LIGHT DIRECTION**

All directions

**DIMMING & LIGHTING CONTROL**

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.*

---

*Technical CE***MATERIAL**

Sphere from fiberglass with epoxy resin, chromed steel pendant

**ENERGY LABEL**

A++ to E

**LIGHTSOURCE TYPE**

Incandescent

**LIGHTSOURCE INCLUDED**

Yes

**NUMBER OF LIGHTSOURCES**

1

**DIAMETER SHADE**

80cm | 31.5"

**INPUT VOLTAGE**

220-240V

**FREQUENCY**

50/60

**MAX POWER CONSUMPTION**

60W

**LAMPHOLDER**

E27

**RECOMMENDED LIGHTSOURCE**

60W MAX type G, 10W LED light included

**LIFETIME**

50000 hours

**CABLE COLOUR**

Black

**CABLE LENGTH**

400cm | 157.5"; 1000cm | 393.7"

**CANOPY**

Pebble II Black, ABS, Pebble II White, ABS

**CRI**

90

**LIGHT DIRECTION**

All directions

**LIGHT OUTPUT**

800 lm

**DIMMING & LIGHTING CONTROL**

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.*

---

*Technical UL***MATERIAL**

Sphere from fiberglass with epoxy resin, chromed steel pendant

**ENERGY LABEL**

A++ to E

**LIGHTSOURCE INCLUDED**

Yes

**DIAMETER SHADE**

80cm | 31.5"

**FREQUENCY**

50/60

**LAMPHOLDER**

E26

**LIFETIME**

50000 hours

**CABLE LENGTH**

400cm | 157.5"; 1000cm | 393.7"

**CRI**

90

**LIGHT OUTPUT**

800 lm

**LIGHTSOURCE TYPE**

Incandescent

**NUMBER OF LIGHTSOURCES**

1

**INPUT VOLTAGE**

110-130V

**MAX POWER CONSUMPTION**

60W

**RECOMMENDED LIGHTSOURCE**

60W MAX type G, 10W LED light included

**CABLE COLOUR**

Black

**CANOPY**

Pebble II Black, ABS, Pebble II White, ABS

**LIGHT DIRECTION**

All directions

**DIMMING & LIGHTING CONTROL**


Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.*

## Random Light II / small

### Dimensions

Ø50cm | 19.7"



### Product

**WIDTH** 50cm | 19.7"

**HEIGHT** 50cm | 19.7"

**DEPTH** 50cm | 19.7"

**DIAMETER** 50cm | 19.7"

**WEIGHT NETTO** 1.2kg | 2.65lbs

### Packaging

**WIDTH** 51cm | 20.1"

**HEIGHT** 53cm | 20.9"

**CUBAGE** 0.14m<sup>3</sup> | 4.87ft<sup>3</sup>

**LENGTH** 51cm | 20.1"

**WEIGHT** 2.5kg | 5.51lbs

### Technical CCC

**MATERIAL**

Sphere from fiberglass with epoxy resin, chromed steel pendant

**ENERGY LABEL**

A++ to E

**LIGHTSOURCE INCLUDED**

Yes

**DIAMETER SHADE**

50cm | 19.7"

**FREQUENCY**

50/60

**LAMPHOLDER**

E27

**LIFETIME**

50000 hours

**CABLE LENGTH**

400cm | 157.5"; 1000cm | 393.7"

**CRI**

90

**LIGHT OUTPUT**

800 lm

**LIGHTSOURCE TYPE**

Incandescent

**NUMBER OF LIGHTSOURCES**

1

**INPUT VOLTAGE**

220-240V

**MAX POWER CONSUMPTION**

60W

**RECOMMENDED LIGHTSOURCE**

60W MAX type G, 10W LED light included

**CABLE COLOUR**

Black

**CANOPY**

Pebble II Black, ABS, Pebble II White, ABS

**LIGHT DIRECTION**

All directions

**DIMMING & LIGHTING CONTROL**

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.**Technical CE***MATERIAL**

Sphere from fiberglass with epoxy resin, chromed steel pendant

**ENERGY LABEL**

A++ to E

**LIGHTSOURCE INCLUDED**

Yes

**DIAMETER SHADE**

50cm | 19.7"

**FREQUENCY**

50/60

**LAMPHOLDER**

E27

**LIFETIME**

50000 hours

**CABLE LENGTH**

400cm | 157.5"; 1000cm | 393.7"

**LIGHTSOURCE TYPE**

Incandescent

**NUMBER OF LIGHTSOURCES**

1

**INPUT VOLTAGE**

220-240V

**MAX POWER CONSUMPTION**

60W

**RECOMMENDED LIGHTSOURCE**

60W MAX type G, 10W LED light included

**CABLE COLOUR**

Black

**CANOPY**

Pebble II Black, ABS, Pebble II White, ABS

**CRI**

90

**LIGHT OUTPUT**

800 lm

**LIGHT DIRECTION**

All directions

**DIMMING & LIGHTING CONTROL**

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.*

---

*Technical UL***MATERIAL**

Sphere from fiberglass with epoxy resin, chromed steel pendant

**ENERGY LABEL**

A++ to E

**LIGHTSOURCE TYPE**

Incandescent

**LIGHTSOURCE INCLUDED**

Yes

**NUMBER OF LIGHTSOURCES**

1

**DIAMETER SHADE**

50cm | 19.7"

**INPUT VOLTAGE**

110-130V

**FREQUENCY**

50/60

**MAX POWER CONSUMPTION**

60W

**LAMPHOLDER**

E26

**RECOMMENDED LIGHTSOURCE**

60W MAX type G, 10W LED light included

**LIFETIME**

50000 hours

**CABLE COLOUR**

Black

**CABLE LENGTH**

400cm | 157.5"; 1000cm | 393.7"

**CANOPY**

Pebble II Black, ABS, Pebble II White, ABS

**CRI**

90

**LIGHT DIRECTION**

All directions

**LIGHT OUTPUT**

800 lm

**DIMMING & LIGHTING CONTROL**

Mains dimmable with compatible light source

*See last page for more information about the dimming possibilities.*



## *Dimming & Lighting Control*

### *Mains dimmable with compatible light source*

Compatible models: large CE, large UL, medium CE, medium UL, small CE, small UL

---