

Statistocrat Suspended Lamp

ATELIER VAN LIESHOUT



This futuristic lamp is a three-dimensional elaboration of the data structure that rule and define the city's well-being, dressed in the sleek slenderness of an efficient aluminium body. A carbon model of serious lightness, the Statistocrat Suspended Lamp is not only the perfect functional lamp, but a reminder that everything is possible if you invest your energy and knowledge in a good plan!

Detailing



Statistocrat features Joep van Lieshout's signature raw weld finish.

Colours



RAL 1004
Golden yellow



RAL 1013
Oyster white



RAL 1023
Traffic yellow



RAL 1027
Curry



RAL 2000
Yellow orange



RAL 2002
Vermilion



RAL 2004
Pure orange



RAL 3003
Ruby red



RAL 3012
Beige red



RAL 3015
Light pink



RAL 5003
Sapphire blue



RAL 5008
Grey blue




RAL 5024
Pastel blue



RAL 6010
Grass green




RAL 6021
Pale green



RAL 7001
Silver grey



RAL 7011
Iron grey



RAL 7035
Light grey



RAL 7044
Silk grey



RAL 8001
Ochre brown



RAL 8014
Sepia brown




RAL 8016
Mahogany brown



RAL 9005
Jet black



RAL 9010
Pure white




RAL 9016
Traffic white


Statistocrat Suspended Lamp

Dimensions


115cm | 45.3"



72cm | 28.3"



38cm | 14.9"



19cm | 7.5"
5cm | 2"

Product

WIDTH 115cm | 45.3"

HEIGHT 38cm | 15"

DEPTH 72cm | 28.3"

WEIGHT NETTO 15kg | 33.07lbs

Packaging

WIDTH 80cm | 31.5"

HEIGHT 45cm | 17.7"

CUBAGE 0.43m³ | 15.26ft³

LENGTH 120cm | 47.2"

WEIGHT 19.5kg | 42.99lbs

Technical CE

MATERIAL

Aluminium frame with structured matt powdercoating.

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

5

INPUT VOLTAGE

220-240

MAX POWER CONSUMPTION

40W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

CANOPY

Matching steel cylinder

CRI

80

LIGHT OUTPUT

1347 lm

See last page for more information about the dimming possibilities.



Technical cULus

MATERIAL

Aluminium frame with structured matt powdercoating.

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

5

INPUT VOLTAGE

100-120

MAX POWER CONSUMPTION

40W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

CANOPY

Matching steel cylinder

CRI

80

LIGHT OUTPUT

1347 lm



Dimming & Lighting Control

Mains, Trailing edge, Reverse phase

The luminaire is dimmable by using an external Electronic Low Voltage dimmer. The dimmer is usually mounted on an existing wall socket and there is no need to change your home's wiring. On the dimmer it should show that it is a LED dimmer, suitable for 5 Watts or lower and C-type capable. Dimming is less fluent and can come with some flicker, a beep or a buzz.

Compatible models: Statistocrat Suspended Lamp CE, Statistocrat Suspended Lamp cULus
